Exhibit A

COPY

4.6.1.5 User Interface

The ACT Manager's user interface (UI) will consist of HTML information pages that will be viewed through the ACT's Web browser. [...] consist of at least two frames, one of which [...] preferences to [...] will contain the [...]

We will use JavaScript functions to enhance the behavior of the forms in the UI. JavaScript will allow us to write event handling functions to perform routine data validation on the form prior to submitting it to a CGI (Common Gateway Interface) program running on the server—a performance and usability enhancement.

10/14/2004 2:25:27 PM

Page 1 of 3

COPY

Specific online help will be provided for each form; a separate help window will open when the user requests help by pushing the help button on the form.

4.6.1.5 ACT Utilities Interface

The ACT Utilities component is new for the ACT. The ACT Manager will send messages to ACT Utilities as part of the [illegible] update process. The ACT Utilities [illegible] listed in etc/services on the AS/400. A socket will be used to communicate with ACT Utilities [illegible] Changes for a particular user or terminal [illegible] The ACT Manager needs to locate the terminal where the new preference [illegible] should be applied. The ACT Manager will use the following [illegible] to locate the target ACT terminal.

- The ACT Manager [illegible text heavily degraded]

- The ACT Manager [illegible text heavily degraded]

A message [illegible] needs to be defined between the ACT Manager and ACT Utilities. Following is the complete list of messages sent to ACT Utilities.

Tell ACT Utilities to reboot the terminal. ACT Utilities will [illegible] displays the reboot message and [illegible] the terminal.

Field Name	Field Value
Command ID	[illegible]
[illegible] Password	[illegible]
[illegible]	[illegible]
Reboot Timing	int num_sec /* [illegible] */
	/* [illegible] */
	/* [illegible] */
Reboot Message	[illegible]

Tell ACT Utilities that a user preference file has changed for a particular workstation. The ACT Utilities uses the target HostID to verify the user is still logged on. The ACT Utilities [illegible] to locate the X Server files to auto-load. The ACT Utilities will reload the X Server files in the normal order for control of the system, then [illegible].

Field Name	Field Value
Command ID	USER_PREF_AVAILABLE
[illegible] Password	[illegible]
Target Host ID	[illegible]
Client App	[illegible]
Application Timing	int num_sec /* 0 apply changes now */
	/* >0 apply after delay */

10/14/2004 2:25:27 PM

PAGE 27/42 * RCVD AT 7/20/2005 11:00:49 AM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/29 * DNIS:2738300 * CSID:5072532382 * DURATION (mm-ss):17-50

COPY   ACT SAI

/* -1 apply at next logoff */

Tell ACT Utilities to display a Pop-up informational message sent by an administrator:

Field Name	Field Value
Command ID	DISPLAY MESSAGE
Config'd Password	
Target User ID	
Message	String message text

Query ACT Utilities for the current logged on UserID and password. This is used by the ACT Manager CGI to learn which user is talking to it from the browser.

Field Name	
Command ID	
Config'd Password	

Reply from ACT Utilities containing current UserID

Field Name	
Command ID	
UserID	
Password	

10/14/2004 2:25:27 PM